

## SA Rod end SAL30-T-K-DURBAL - SAL30-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal30-t-k-durbal>

### SAL30-T-K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**male thread:** maintenance free, according to DIN ISO 12240-4, series K

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	measurement [mm]		C <sub>1</sub>	d <sub>2</sub>
	right hand thread	left hand thread		
SAL 30 T/K	30	M 30 x 2	37	25,00

  

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
SA / SAL 30 T/K	66	35	110	17	114,0	1,100

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490403
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	70 mm
Outside diameter	2.756" inch
Thickness	37 mm
Thickness	1.457" inch
Type	SA
Weight	1100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)  
 02038 087 274  
 CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE