

## SA Rod end SSA28-T-K-DURBAL - SSA28-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/ssa28-t-k-durbal>

### SSA28-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]			
SSA 28 T/K	28		G	B	C1	d2
			M 27 x 2	35	24,00	66

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 28 T/K	62	33	103	15	107,0	0,800

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490991
Inside diameter	28 mm
Outside diameter	66 mm
Thickness	35 mm
Type	SA
Weight	800 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE