

SI Rod end

DSSI5-T-K-DURBAL - DSSI5-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/dssi5-t-k-durbal>

DSSI5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | |
|--------------|-------------------|------------------|------------------|----------------|----------------|----------------|----------------|----------------|--|
| | d | G | B | C ₁ | d ₁ | d ₂ | d ₃ | d ₄ | |
| DSSI 5 T/K | 5 | M 5 | 8 | 6,00 | 18 | 8,5 | 11 | | |

| type | l ₁ min | W | h | α | load rating C ₀ [kN] | weight [kg] |
|--------------------|--------------------|---|----|----|---------------------------------|-------------|
| DSSI / DSSIL 5 T/K | 10 | 9 | 27 | 13 | 6,0 | 0,016 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952491059 |
| Inside diameter | 5 mm |
| Outside diameter | 18 mm |
| Thickness | 8 mm |
| Type | SI |
| Weight | 16 g |
| Thread | Right-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE