

## SI Rod end DSSIL5-T-K-DURBAL - DSSIL5-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/dssil5-t-k-durbal>

### DSSIL5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 5 T/K			d	G	B	C1	d1	d2	d3	d4
			5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]			α °FS	load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	W	h			
DSSIL / DSSIL 5 T/K	10	9	27	13	6,0	0,016

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491080
Inside diameter	5 mm
Inside diameter	0.197" inch
Outside diameter	18 mm
Outside diameter	0.709" inch
Thickness	8 mm
Thickness	0.315" inch
Type	SI
Weight	16 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE