

SI Rod end

SSI10-T-K-DURBAL - SSI10-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/ssi10-t-k-durbal>

SSI10-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
			d	G	B	C1	d1	d2	d3	d4
SSI 10 T/K			10	M 10	14	10,50	28	15,0	19	

type	measurement [mm]				load rating C ₀ [kg]	weight [g]
	l ₁ min	W	h	α [°]		
SSI / SSI10 T/K	20	17	43	13	18,0	0,077

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491196
Inside diameter	10 mm
Outside diameter	28 mm
Thickness	14 mm
Type	SI
Weight	77 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE