

SI Rod end SSIL18-T-K-DURBAL - SSIL18-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/ssil18-t-k-durbal>

SSIL18-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 18 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			18	M 18 x 1,5	23	16,50	44	25,0	31	

type	measurement [mm]				load rating C ₀ [kg]	weight [g]
	l ₁ min	W	h	α [°]		
SSI / SSIL 18 T/K	32	27	71	15	47,5	0,320

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491493
Inside diameter	18 mm
Inside diameter	0.709" inch
Outside diameter	44 mm
Outside diameter	1.732" inch
Thickness	23 mm
Thickness	0.906" inch
Type	SI
Weight	320 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE