

SI Rod end
SSI22-T-K-DURBAL - SSI22-T-K-DURBAL
<https://www.123bearing.co.uk/bearing-housing/rod-end/si/ssi22-t-k-durbal>

SSI22-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSI 22 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			22	M 22 x 1,5	28	20,00	54	30,0		38

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h				
SSI / SSI 22 T/K	37	32	84	15	68,0	0,540	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491608
Inside diameter	22 mm
Inside diameter	0.866" inch
Outside diameter	54 mm
Outside diameter	2.126" inch
Thickness	28 mm
Thickness	1.102" inch
Type	SI
Weight	540 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE