

## SI Rod end

### DSIL10-PK-DURBAL - DSIL10-PK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/dsil10-pk-durbal>

#### DSIL10-PK



**female thread; maintenance free, according to DIN ISO 12240-4, series K**

**Description:** DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

**rod end body: carbon case plated**

**Sliding combination: steel / bronze-PTFE composite**

**inner ring: bearing steel hardened and ground**

**Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite**

**Lubrication: maintenance free**

order number	d	G	measurement (mm)				
right hand thread	10	M 10	14	11,00	29	15,0	19
<b>DSIL 10 PK</b>							

type	l <sub>1</sub> min	measurement (mm)		alpha [°]	load rating C <sub>0</sub> (N)	weight (kg)
<b>DSI / DSIL 10 PK</b>	20	17	43	12	18,00	0,077

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491899
Inside diameter	10 mm
Outside diameter	29 mm
Thickness	14 mm
Type	SI
Weight	77 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE