

SI Rod end DSIL20-PK-DURBAL - DSIL20-PK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/dsil20-pk-durbal>

DSIL20-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

End end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement (mm)					
right hand thread	d	G	B	C1	d2	d4
DSIL 20 PK	20	M 20 x 1,5	25	18,00	51	27,5

type	measurement (mm)				load rating C ₀ (kN)	weight (kg)
	l ₁ min	w	h	α [°]		
DSI / DSIL 20 PK	33	30	77	14	57,00	0,420

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492216
Inside diameter	20 mm
Inside diameter	0.787" inch
Outside diameter	51 mm
Outside diameter	2.008" inch
Thickness	25 mm
Thickness	0.984" inch
Type	SI
Weight	420 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE