

SA Rod end DSA16-BK-DURBAL - DSA16-BK-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/dsa16-bk-durbal>

DSA16-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated
sliding combination:
steel / bronze-PTFE composite
inner ring:
bearing steel hardened and ground
Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
DSA 16 BK	16	M 16	21	15,0	43

type	measurement [mm]		load rating C ₀ (kN)	weight (kg)
	l ₁ min	h		
DSA / DSAL 16 BK	40	66	39,00	0,210

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492568
Inside diameter	16 mm
Inside diameter	0.63" inch
Outside diameter	43 mm
Outside diameter	1.693" inch
Thickness	21 mm
Thickness	0.827" inch
Type	SA
Weight	210 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE