

## SA Rod end DSA16-BK-DURBAL - SA16-BK-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sa16-bk-durbal>

### DSA16-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated  
sliding combination:  
steel / bronze-PTFE composite  
inner ring:  
bearing steel hardened and ground  
Outer ring:  
rod end body pressed around, outer race  
lined with bronze-PTFE composite  
Lubrication:  
maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C <sub>1</sub>	d <sub>2</sub>
DSA 16 BK	16	M 16	21	15,0	43

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	h			
DSA / DSAL 16 BK	40	66	14	39,00	0,210

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492568
Inside diameter	16 mm
Outside diameter	43 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE