


SA Rod end
SAL16-BK-DURBAL - SAL16-BK-DURBAL
<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal16-bk-durbal>

SAL16-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:

surface zinc plated

Sliding combination:

steel / bronze-PTFE composite

Inner ring:

bearing steel hardened and ground

Outer ring:

rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication:

maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
SAL 16 BK	16	M 16	21	15,0	43

type	measurement [mm]		alpha [°]	load rating C ₀ [kN]	weight [kg]
	l ₂ min	h			
SA / SAL 16 BK	40	66	14	39,00	0,210

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492582
Inside diameter	16 mm
Outside diameter	43 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE