

## SA Rod end SA20-BK-DURBAL - SA20-BK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sa20-bk-durbal>

### SA20-BK



**male thread:** maintenance free, according to DIN ISO 12240-4, series K

**Description:** DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel hardened and ground

**Outer ring:** rod end body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 20 BK		20	M 20 x 1,5	25	18,0	51

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
SA / SA 20 BK	47	78	14	57,00	0,380

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492650
Inside diameter	20 mm
Outside diameter	51 mm
Thickness	25 mm
Type	SA
Weight	380 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE