

SA Rod end SAL22-BK-DURBAL - DSAL22-BK-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/dsal22-bk-durbal>

SAL22-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]				
	right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 22 BK	22	M 22 x 1,5	22	28	28	20,0	55

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₂ min	h			
SA / SAL 22 BK	50	84	15	68,00	0,480

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492698
Inside diameter	22 mm
Outside diameter	55 mm
Thickness	28 mm
Type	SA
Weight	480 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE