

SA Rod end SA25-BK-DURBAL - SA25-BK-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sa25-bk-durbal>

SA25-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:

surface zinc plated

Sliding combination:

steel / bronze-PTFE composite

Inner ring:

bearing steel hardened and ground

Outer ring:

rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication:

maintenance free

order number	measurement [mm]		C ₁	d ₂
	d	G		
SA 25 BK	25	M 24 x 2	31	61

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
SA / SA 25 BK	57	94	15	85,00	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492735
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE