

SA Rod end
SAL25-BK-DURBAL - SAL25-BK-DURBAL
<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal25-bk-durbal>

SAL25-BK



male thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel hardened and ground

Outer ring: rod end pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement [mm]	
	right hand thread	left hand thread
SAL 25 BK	25	M 24 x 2

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
SA / SAL 25 BK	57	94	15	85,00	0,640

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492742
Inside diameter	25 mm
Outside diameter	61 mm
Thickness	31 mm
Type	SA
Weight	640 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk
02038 087 274
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE