

SA Rod end GAL8-UK-DURBAL - GAL8-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/gal8-uk-durbal>

GAL8-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



| order number | | measurement (mm) | | | | | |
|-------------------|------------------|------------------|-----|---|----------------|----------------|--|
| right hand thread | left hand thread | d | g | s | C ₁ | d ₂ | |
| | GAL 8 UK | 8 | M 8 | 8 | 6,0 | 24 | |

| type | measurement (mm) | | h | α [°] | load rating C ₀ [kN] | weight (kg) |
|----------------|--------------------|--------------------|----|-------|------------------------------------|----------------|
| | l ₁ min | l ₂ min | | | | |
| GAR / GAL 8 UK | 22 | 14 | 42 | 15 | 12,9 | 0,029 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952492810 |
| Inside diameter | 8 mm |
| Outside diameter | 24 mm |
| Thickness | 8 mm |
| Type | SA |
| Weight | 29 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE