

SA Rod end GAR15-UK-DURBAL - GAR15-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/gar15-uk-durbal>


GAR15-UK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C1	d2
GAR 15 UK	15	M 14	12	10,0	40

type	measurement [mm]		h	alpha [°]	load rating C ₀ [kN]	weight [kg]
	l, min	l ₁ min				
GAR / GAL 15 UK	34	20	63	8	36,0	0,140

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492933
Inside diameter	15 mm
Outside diameter	40 mm
Thickness	12 mm
Type	SA
Weight	140 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE