

# GE Rod end

## GAR60-UK-2RS-DURBAL - GAR60-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/gar60-uk-2rs-durbal>


### GAR60-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)	
right-hand thread	d	G
left-hand thread	B	C <sub>1</sub>
<b>GAR 60 UK-2RS</b>	60	M 52 x 3
	44	38,0
		135

type	measurement [mm]		h	α [°]	load rating C <sub>0</sub> [kN]	weight (kg)
	l <sub>1</sub> min	l <sub>2</sub> min				
GAR / GAL 60 UK-2RS	115	75	210	6	450,0	5,900

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467782
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	GE
Weight	5900 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE