

SA Rod end GAR80-UK-2RS-DURBAL - GAR80-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/gar80-uk-2rs-durbal>


GAR80-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body ground around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)		measurement (mm)			weight	
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
GAR 80 UK-2RS		80	M 64 x 4	55	47,0	180	
type	l ₁ min	l ₂ min	h	α [°]	load rating C ₀ [kN]	weight [kg]	
GAR / GAL 80 UK-2RS	140	100	270	6	750,0	12,000	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493541
Inside diameter	80 mm
Outside diameter	180 mm
Thickness	55 mm
Type	SA
Weight	12000 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE