

SI Rod end GIL6-UK-DURBAL - GIL6-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gil6-uk-durbal>

GIL6-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



| order number | d | G | B | measurement [mm] | | | |
|-------------------|---|-----|---|------------------|----------------|----------------|----------------|
| right hand thread | | | | C ₁ | d ₂ | d ₃ | d ₄ |
| GIL 6 UK | 6 | M 6 | 6 | 4,4 | 21 | 10,0 | 13 |

| type | measurement [mm] | | | α [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----|----|-----------------|---------------------------------------|----------------|
| | t ₃ min | h | W | | | |
| GIR / GIL 6 UK | 11 | 30 | 11 | 13 | 8,2 | 0,021 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952493589 |
| Inside diameter | 6 mm |
| Outside diameter | 21 mm |
| Thickness | 6 mm |
| Type | SI |
| Weight | 21 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE