

SI Rod end GIL6-UK-DURBAL - GIL6-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gil6-uk-durbal>

GIL6-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]				
right hand thread				C ₁	C ₂	d ₂	d ₃	d ₄
GIL 6 UK	6	M 6	6	4,4	21	10,0	13	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 6 UK	11	30	11	13	8,2	0,021

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493589
Inside diameter	6 mm
Outside diameter	21 mm
Thickness	6 mm
Type	SI
Weight	21 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE