

## SI Rod end GIR15-UK-DURBAL - DGIR15-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/dgir15-uk-durbal>

### GIR15-UK



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Rod end body:** surface zinc plated

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIR 15 UK	15	M 14	12	10,0	40	21,0	26

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIR 15 UK	30	61	22	8	36,0	0,180

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493725
Inside diameter	15 mm
Outside diameter	40 mm
Thickness	12 mm
Type	SI
Weight	180 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE