

SI Rod end GIL15-UK-DURBAL - GIL15-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gil15-uk-durbal>

GIL15-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]	d ₂	d ₃	d ₄
GIL 15 UK	15	M 14	12	10,0	40	21,0	26

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 15 UK	30	61	22	8	36,0	0,180

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493732
Inside diameter	15 mm
Outside diameter	40 mm
Thickness	12 mm
Type	SI
Weight	180 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE