

SI Rod end GIR20-UK-2RS-DURBAL - GIR20-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gir20-uk-2rs-durbal>

GIR20-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]						
right hand thread	d	G	B	C ₁	C ₂	d ₂	d ₄
GIR 20 UK (-2RS)	20	M 20 x 1,5	16	13,0	53	27,5	35
type	measurement [mm]			load rating	weight		
GIR / GIL 20 UK	t ₃ min	h	W	C ₀ [kN]	[kg]		
	40	77	32	9	60,0	0,350	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952493855
Inside diameter	20 mm
Inside diameter	0.787" inch
Outside diameter	53 mm
Outside diameter	2.087" inch
Thickness	16 mm
Thickness	0.63" inch
Type	SI
Weight	350 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE