

SI Rod end GIR25-UK-DURBAL - GIR25-UK-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gir25-uk-durbal>

GIR25-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

| order number | measurement [mm] | | | | | |
|--------------|------------------|----------|----|----------------|----------------|-------------------------------|
| GIR 25 UK | d | G | B | C ₁ | C ₂ | d ₂ d ₄ |
| | 25 | M 24 x 2 | 20 | 17,0 | 64 | 33,5 42 |

| type | measurement [mm] | | | α [°] | load rating C ₀ [kN] | weight [kg] |
|-----------------|--------------------|----|----|-------|---------------------------------|-------------|
| | l ₃ min | h | W | | | |
| GIR / GIR 25 UK | 48 | 94 | 36 | 7 | 83,0 | 0,640 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952493978 |
| Inside diameter | 25 mm |
| Outside diameter | 64 mm |
| Thickness | 20 mm |
| Type | SI |
| Weight | 640 g |
| Thread | Right-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE