

# SI Rod end GIL35-UK-2RS-DURBAL - GIL35-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gil35-uk-2rs-durbal>

## GIL35-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	d	G	B	measurement [mm]			
right hand thread				C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>
GIL 35 UK-2RS	35	M 36 x 3	25	21,0	82	47,0	58

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIL 35 UK-2RS	60	125	50	6	146,0	1,300

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494098
Inside diameter	35 mm
Outside diameter	82 mm
Thickness	25 mm
Type	-
Weight	1300 g
Thread	-
Lubrication	-
Packaging	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE