

SI Rod end GIR45-UK-2RS-DURBAL - GIR45-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gir45-uk-2rs-durbal>

GIR45-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Rod end body: surface zinc plated

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
			d	G	B	C ₁	d ₂	d ₄	
GIR 45 UK-2RS			45	M 42 x 3	32	27,0	102	58,0	70

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 45 UK-2RS	65	145	60	7	240,0	2,500

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494166
Inside diameter	45 mm
Outside diameter	102 mm
Thickness	32 mm
Type	SI
Weight	2500 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE