

SI Rod end GIL70-UK-2RS-DURBAL - GIL70-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gil70-uk-2rs-durbal>

GIL70-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	measurement [mm]	d ₂	d ₃	d ₄
GIL 70 UK-2RS	70	M 56 x 4	49	42,0	160	80,0	98

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 70 UK-2RS	80	200	85	6	610,0	8,600

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494289
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SI
Weight	8600 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE