

SI Rod end GIL80-UK-2RS-DURBAL - GIL80-UK-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/gil80-uk-2rs-durbal>

GIL80-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number with hand thread
GIL 80 UK-2RS

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	t_2 min	h	W			
GIR / GIL 80 UK-2RS	85	230	100	6	750,0	12,000

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494333
Inside diameter	80 mm
Inside diameter	3.15" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	55 mm
Thickness	2.165" inch
Type	SI
Weight	12000 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE