

SA Rod end POS8-DURBAL - POS8-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/pos8-durbal>

POS8



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread; maintenance free, according to DIN ISO 12240-4, series K



Rod end body: surface zinc plated
Sliding combination: steel / heavy duty bronze
Inner ring: bearing steel, hardened, ground and spherical surface chromium plated
Outer ring: heavy duty bronze with lubrication
Lubrication: lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	B	G	M	B	C ₁	d ₁	
POS 8	8	M 8		12	9,00	22	

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 8	25	42	14	11,6	0,030

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494449
Inside diameter	8 mm
Outside diameter	22 mm
Thickness	12 mm
Type	SA
Weight	30 g
Thread	Right-hand thread
Lubrication	without
Packaging	-
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE