

SA Rod end POSL8-DURBAL - POSL8-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/posl8-durbal>

POSL8



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

order number		measurement [mm]	
right hand thread	left hand thread	B	C ₁ d ₁
POSL 8		8 M 8	12 9,00 22

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 8	25	42	14	11,6	0,030

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494456
Inside diameter	8 mm
Outside diameter	22 mm
Thickness	12 mm
Type	-
Weight	30 g
Thread	-
Lubrication	-
Packaging	-
Standard	-

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE