

## SA Rod end POS16-DURBAL - POS16-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/pos16-durbal>

### POS16



**Description:** DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



rod end body:  
surface zinc plated

Sliding combination:  
steel / heavy duty bronze

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
heavy duty bronze with lubrication

Lubrication:  
lubrication required

order number	measurement [mm]		measurement [mm]		
	right hand thread	left hand thread	B	C <sub>1</sub>	d <sub>1</sub>
POS 16	16	M 16	21	15,00	40

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
POS / POSL 16	40	66	15	28,5	0,210

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494616
Inside diameter	16 mm
Outside diameter	40 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE