

SI Rod end
SIZP15-S-DURBAL - SIZP15-S-DURBAL
<https://www.123bearing.co.uk/bearing-housing/rod-end/si/sizp15-s-durbal>

SIZP15-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

order number	right hand thread		left hand thread		measurement [mm]							
	d	G	B	C1	d2	d3	d4	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SIZP 15 S	15,88	5/8 - 18	19,05	14,27	38,10	21,84	25,40					

type	inches	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W				
SIZP / SIZPL 15 S	5 / 8 "	38,10	22,23	63,50	11	21,0	0,190

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952495866
Inside diameter	15.88 mm
Outside diameter	38.1 mm
Thickness	19.05 mm
Type	SI
Weight	190 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk
02038 087 274
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE