

SI Rod end
SIZP25-S-DURBAL - SIZP25-S-DURBAL
<https://www.123bearing.co.uk/bearing-housing/rod-end/si/sizp25-s-durbal>

SIZP25-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIZP 25 S		25,40	5/8 - 12	34,93	25,40	69,85	37,72	44,45

type	inches	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W	h			
SIZP / SIZPL 25 S	1"	53,98	38,10	104,78	14	101,0	1,000

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952495941
Inside diameter	25.4 mm
Outside diameter	69.85 mm
Thickness	34.93 mm
Type	SI
Weight	1000 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk
02038 087 274
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE