

SA Rod end SAZP9-S-DURBAL - SAZP9-S-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sazp9-s-durbal>

SAZP9-S



male thread:
lubrication required, similar to DIN ISO 12240-4; series R, measurement in inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SAZP 9 S		9,53	3/8 - 24
			B
			C1
			d2

type	inches	measurement [mm]		α	load rating C ₀ [kN]	weight [g]
		h min	h	[°]		
SAZP / SAZPL 9 S	3 / 8 "	31,75	49,23	9	10,0	0,055

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496115
Inside diameter	9.53 mm
Outside diameter	25.4 mm
Thickness	12.7 mm
Type	SA
Weight	55 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE