

SA Rod end DSAZPL25-S-DURBAL - DSAZPL25-S-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/dsazpl25-s-durbal>

DSAZPL25-S



male thread:
lubrication required, similar to DIN ISO 12240-4; series R, measurement in inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

| order number | | measurement [mm] | |
|-------------------|------------------|------------------|----------------|
| right hand thread | left hand thread | B | C ₁ |
| DSAZPL 25 S | | 25,40 | 69,85 |

| type | inches | measurement [mm] | | α [°] | load rating C ₀ [kN] | weight [kg] |
|---------------------|--------|------------------|--------|-------|---------------------------------|-------------|
| | | h min | h | | | |
| DSAZP / DSAZPL 25 S | 1" | 53,98 | 104,78 | 14 | 101,0 | 1,100 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952496320 |
| Inside diameter | 25.4 mm |
| Outside diameter | 69.85 mm |
| Thickness | 34.93 mm |
| Type | SA |
| Weight | 1100 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE