

## SA Rod end SAZJL9-DURBAL - SAZJL9-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sazjl9-durbal>


### SAZJL9



female thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches



**Description:** DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size  $\geq 9$  with grease nipple can be mounted upon request.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
SAZJL	9	9,53	3/8 - 24	12,70	9,12	25,40	
type	inches	measurement [mm] l <sub>1</sub> min	h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]	
SAZI / SAZJL	9	3 / 8 "	31,75	49,23	11,0	16,0	0,050

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496467
Inside diameter	9.53 mm
Inside diameter	3/8" inch
Outside diameter	25.4 mm
Outside diameter	1" inch
Thickness	12.7 mm
Thickness	1/2" inch
Type	SA
Weight	50 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE