

SI Rod end SIZJ4-DURBAL - SIZJ4-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/sizj4-durbal>


SIZJ4



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon request.



Rod end body:
surface zinc plated
Sliding combination:
steel / steel
Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated
Outer ring:
rod end body pressed around inner ring
Lubrication:
lubrication required

order number	right hand thread	left hand thread	measurement [mm]						
SIZJ 4			d	B	C ₁	d ₂	G	d ₃	d ₄
			4,83	7,92	5,94	15,88	10 - 32	7,54	10,31
type	inches	h ₁ min	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [g]	
SIZJ / SIZJL 4		12,70	7,92	26,97	10,0		6,8	0,018	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496665
Inside diameter	4.83 mm
Outside diameter	15.88 mm
Thickness	7.92 mm
Type	SI
Weight	18 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE