

SI Rod end SIZJL11-DURBAL - SIZJL11-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/sizjl11-durbal>

SIZJL11



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJL 11	11,10	14,27	10,31	28,58	7/16 - 20	15,49	19,05

type	inches	h ₁ min	measurement [mm]	h	α [°]	load rating C ₀ [kN]	weight [kg]
SIZJ / SIZJL 11	7 / 16 "	22,23	15,88	46,02	10,5	21,0	0,082

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496832
Inside diameter	11.1 mm
Inside diameter	0.437" inch
Outside diameter	28.58 mm
Outside diameter	1 1/8" inch
Thickness	14.27 mm
Thickness	0.562" inch
Type	SI
Weight	82 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE