

SI Rod end SI20-ES-2RS-DURBAL - SI20-ES-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si20-es-2rs-durbal>

SI20-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

| order number | | measurement (mm) | | | | | | |
|-------------------|------------------|------------------|------------|----|------|----|------|----|
| right hand thread | left hand thread | d | G | B | C1 | d2 | d3 | d4 |
| SI 20 ES (-2RS) | | 20 | M 20 x 1.5 | 16 | 13,0 | 53 | 27,5 | 35 |

| type | measurement [mm] | | | α [°] | load rating C_0 [kN] | weight [kg] |
|-----------------------|------------------|----|----|--------------|------------------------|-------------|
| | l_1 min | W | h | | | |
| SI / SIL 20 ES (-2RS) | 40 | 32 | 77 | 9 | 60,0 | 0,35 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952497105 |
| Inside diameter | 20 mm |
| Inside diameter | 0.787" inch |
| Outside diameter | 53 mm |
| Outside diameter | 2.087" inch |
| Thickness | 16 mm |
| Thickness | 0.63" inch |
| Type | SI |
| Weight | 350 g |
| Thread | Right-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE