

## SI Rod end SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si25-es-2rs-durbal>

### SI25-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**order number**  
right hand thread    left hand thread

SI 25 ES (-2RS)	measurement [mm]		measurement [mm]				measurement [mm]							
	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	type	l <sub>3</sub> min	W	h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SII 25 ES (-2RS)	25	M 24 x 2	20	17,0	64	33,5	42	SI	48	36	94	7	83,0	0,64

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497198
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SI
Weight	640 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE