

SI Rod end SI40-ES-2RS-DURBAL - SI40-ES-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si40-es-2rs-durbal>

SI40-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number

right hand thread	left hand thread	measurement (mm)					
d	G	B	C ₁	d ₂	d ₃	d ₄	
SI 40 ES (-2RS)	M 39 x 3	28	23,0	92	52,0	65	

measurement [mm]

type	l ₁ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SII 40 ES (-2RS)	65	55	142	7	180,0	2,0

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497389
Inside diameter	40 mm
Outside diameter	92 mm
Thickness	28 mm
Type	SI
Weight	2000 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE