

SI Rod end SIL50-ES-DURBAL - SIL50-ES-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/sil50-es-durbal>

SIL50-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)					
		d	G	B	C ₁	d ₂	d ₄
SIL 50 ES		50	M 45 x 3	35	30,0	112	75

type

	l ₁ min	W	h	α [°]	load rating C ₀ (kN)	weight (kg)
SI / SIL 50 ES	68	65	160	6	290,0	3,5

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497587
Inside diameter	50 mm
Inside diameter	1.969" inch
Outside diameter	112 mm
Outside diameter	4.409" inch
Thickness	35 mm
Thickness	1.378" inch
Type	SI
Weight	3500 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE