

SI Rod end SI70-ES-DURBAL - SI70-ES-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si70-es-durbal>

SI70-ES



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 70 ES		70	M 56 x 3	49	42,0	160	80,0	98

type	measurement [mm]			α [°]	load rating C_p [kN]	weight [kg]
	l_1 min	W	h			
SI / SII 70 ES	80	85	200	6	610,0	8,6

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497747
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SI
Weight	8600 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE