

## SI Rod end SI80-ES-DURBAL - SI80-ES-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si80-es-durbal>

### SI80-ES



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread	measurement (mm)					
d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	
SI 80 ES	80	M 64 x 4	55	47,0	180	95,0	110

  

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	W	h	$\alpha$ [°]		
SI / SIL 80 ES	85	100	230	6	750,0	12,0

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497792
Inside diameter	80 mm
Outside diameter	180 mm
Thickness	55 mm
Type	SI
Weight	12000 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE