

## SA Rod end SAL6-E-DURBAL - SAL6-E-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal6-e-durbal>

### SAL6-E



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


**Ball end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
	<b>SAL 6 E</b>	6	M 6	6	4,4	21	

type	measurement [mm]			n	load rating	weight
	l <sub>1</sub> min	l <sub>2</sub>	h	[°]	C <sub>0</sub> [kN]	[kg]
SA / SAL 6 E	18	11	36	13	8,2	0,017

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497877
Inside diameter	6 mm
Inside diameter	0.236" inch
Outside diameter	21 mm
Outside diameter	0.827" inch
Thickness	6 mm
Thickness	0.236" inch
Type	SA
Weight	17 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE