

## SA Rod end SAL17-ES-DURBAL - SAL17-ES-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal17-es-durbal>

### SAL17-ES



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
	<b>SAL 17 ES</b>	17	M 16	14	11,0	46	
type		measurement [mm]		n	load rating	weight	
		l <sub>1</sub> min	l <sub>2</sub>	[°]	C <sub>0</sub> [kN]	[kg]	
SA /	SAL 17 ES	36	23	69	10	45,0	0,190

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498102
Inside diameter	17 mm
Outside diameter	46 mm
Thickness	14 mm
Type	SA
Weight	190 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE