

SA Rod end SA17-ES-DURBAL - SA17-ES-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sa17-es-durbal>

SA17-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 17 ES		17	M 16	14	11,0	46

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SA L 17 ES	36	23	69	10	45,0	0,190

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498157
Inside diameter	17 mm
Outside diameter	46 mm
Thickness	14 mm
Type	SA
Weight	190 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE