

## SA Rod end SA25-ES-2RS-DURBAL - SA25-ES-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sa25-es-2rs-durbal>

### SA25-ES-2RS



**male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

**Ball end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 25 ES (-2RS)		25	M 24 x 2	20	17,0	64

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 25 ES (-2RS)	53	32	94	7	83,0	0,560	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498300
Inside diameter	25 mm
Outside diameter	64 mm
Thickness	20 mm
Type	SA
Weight	560 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE